

Docket No. 198004US2



2712

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF: Kohji SAKAI, et al.

SERIAL NO: 09/678,611

GAU: 2712

FILED: October 4, 2000

EXAMINER:

FOR: SCANNING OPTICAL SYSTEM, OPTICAL SCANNING DEVICE AND IMAGE FORMING APPARATUS

INFORMATION DISCLOSURE STATEMENT UNDER 37 CFR 1.97

COMMISSIONER FOR PATENTS
ALEXANDRIA, VIRGINIA 22313

RECEIVED

APR 20 2004

SIR:

Applicant(s) wish to disclose the following information.

Technology Center 2600

REFERENCES

- ☐ The applicant(s) wish to make of record the references listed on the attached form PTO-1449. Copies of the listed references are attached, where required, as are either statements of relevancy or any readily available English translations of pertinent portions of any non-English language references.
- ☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

RELATED CASES

- ☒ Attached is a list of Applicants' pending application(s) which may be related to the present application. A copy of the claims and drawings of the pending application(s) is attached.
- ☐ A check or credit card payment form is attached in the amount required under 37 CFR §1.17(p).

CERTIFICATION

- ☐ Each item of information contained in this information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of this statement.
- ☒ No item of information contained in this information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application or, to the knowledge of the undersigned, having made reasonable inquiry, was known to any individual designated in 37 CFR §1.56(c) more than three months prior to the filing of this statement.

DEPOSIT ACCOUNT

- ☒ Please charge any additional fees for the papers being filed herewith and for which no check or credit card payment is enclosed herewith, or credit any overpayment to deposit account number 15-0030. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.

Gregory J. Maier

Registration No. 25,599

Joseph A. Scafetta, Jr.
Registration No. 26, 803

Customer Number

22850

Tel. (703) 413-3000
Fax. (703) 413-2220
(OSMMN 05/03)



LIST OF RELATED CASES

<u>Docket Number</u>	<u>Serial or Patent Number</u>	<u>Filing or Issue Date</u>	<u>Inventor/ Applicant</u>
198004US2*	09/678,611	10/04/00	SAKAI et al.
247061US2	10/758,212	01/16/04	SAKAI

RECEIVED

APR 20 2004

Technology Center 2600

*Present Application; listed for information
GJM/sb
I:\EM\EMREL\190s-199s\198004US LIST6.DOC

WHAT IS CLAIMED IS:

1. A synchronous detector that detects timing of scanning by an optical scanner, the optical scanner having a light source that emits a light beam, a deflecting unit that deflects the light beam, a scanning
5 optical element that focuses the light beam deflected by the deflecting unit onto a surface to be scanned, comprising:
a photoreceiver; and
a synchronous optical element that focus the light beam deflected by the deflecting unit onto the photoreceiver, wherein the
10 synchronous optical element satisfies a relationship $f_m < f_d$, where f_m is a composite focal length of the scanning optical element in a main scanning direction, and f_d is a composite focal length of the synchronous optical element in the main scanning direction.
- 15 2. The synchronous detector according to claim 1, wherein the synchronous detector comprises a plurality of the synchronous optical elements and a plurality of the photoreceivers, wherein the synchronous optical elements have negative power in the main scanning direction.
- 20 3. The synchronous detector according to claim 2, wherein a plurality of laser beams travel toward the same synchronous detector, and the synchronous optical elements are arranged so as to focus principal rays of the light beams to a single point in a secondary scanning direction.

25

FOR INFORMATION
DISCLOSURE
PURPOSES ONLY

Related Pending Application

Related Case Serial No: 10/758,212

Related Case Filing Date: 01-16-04

4. The synchronous detector according to claim 1, wherein the synchronous optical element is a single lens that is designed such that one surface thereof is a cylindrical surface that is concave in the main scanning direction, and the other surface thereof is a rotationally
5 symmetric surface.
5. An optical scanner comprising:
a light source that emits a light beam;
a deflecting unit that deflects the light beam;
10 a scanning optical element that focuses the light beam deflected by the deflecting unit onto a surface to be scanned; and
a synchronous detector that detects timing of scanning by an optical scanner, the synchronous detector including
a photoreceiver; and
15 a synchronous optical element that focus the light beam deflected by the deflecting unit onto the photoreceiver, wherein the synchronous optical element satisfies a relationship $f_m < f_d$, where f_m is a composite focal length of the scanning optical element in a main scanning direction, and f_d is a composite focal length of the
20 synchronous optical element in the main scanning direction.
6. The optical scanner according to claim 5, wherein
the light sources are provided in plurality, each of the light sources emits a light beam,
25 the deflecting units are provided in plurality, each of the

deflecting units deflects a corresponding one of the light beam, and
the scanning optical elements are provided in plurality, each of
the scanning optical elements focuses the light beam deflected by a
corresponding one of the deflecting unit onto a corresponding one of a
5 surface to be scanned.

7. The optical scanner according to claim 6, wherein the optical
scanner is a multi-beam optical scanner in which a plurality of light
beams pass through the respective optical surfaces of scanning the
10 optical element having a form in which identical optical surfaces are
formed on top of one another in a plurality of tiers.

8. The optical scanner according to claim 5, wherein the
synchronous detector comprises a plurality of the synchronous optical
15 elements and a plurality of the photoreceivers, wherein the synchronous
optical elements have negative power in the main scanning direction.

9. The optical scanner according to claim 8, wherein a plurality of
laser beams travel toward the same synchronous detector, and the
20 synchronous optical elements are arranged so as to focus principal rays
of the light beams to a single point in a secondary scanning direction.

10. The optical scanner according to claim 5, wherein the
synchronous optical element is a single lens that is designed such that
25 one surface thereof is a cylindrical surface that is concave in the main

scanning direction, and the other surface thereof is a rotationally symmetric surface.

11. An image forming apparatus comprising a photoreceptor, an
5 optical scanner that optically scans a surface of the photoreceptor, and
a synchronous detector that detects timing of scanning of the
photoreceptor by the optical scanner, wherein
the optical scanner includes
a light source that emits a light beam;
10 a deflecting unit that deflects the light beam; and
a scanning optical element that focuses the light beam
deflected by the deflecting unit onto a surface to be scanned, and
the synchronous detector includes
a photoreceiver; and
15 a synchronous optical element that focus the light beam
deflected by the deflecting unit onto the photoreceiver, wherein the
synchronous optical element satisfies a relationship $f_m < f_d$, where f_m is
a composite focal length of the scanning optical element in a main
scanning direction, and f_d is a composite focal length of the
20 synchronous optical element in the main scanning direction.
12. The image forming apparatus according to claim 11, wherein the
synchronous detector comprises a plurality of the synchronous optical
elements and a plurality of the photoreceivers, wherein the synchronous
25 optical elements have negative power in the main scanning direction.

13. The image forming apparatus according to claim 12, wherein a plurality of laser beams travel toward the same synchronous detector, and the synchronous optical elements are arranged so as to focus
5 principal rays of the light beams to a single point in a secondary scanning direction.

14. The image forming apparatus according to claim 11, wherein the synchronous optical element is a single lens that is designed such that
10 one surface thereof is a cylindrical surface that is concave in the main scanning direction, and the other surface thereof is a rotationally symmetric surface.

ABSTRACT OF THE DISCLOSURE

A synchronous detector detects timing of scanning by an optical scanner in an image forming apparatus. The optical scanner has a light source that emits a light beam, a deflecting unit that deflects the light beam, a scanning optical element that focuses the light beam deflected by the deflecting unit onto a surface to be scanned. The synchronous detector includes a photoreceiver, and a synchronous optical element that focus the light beam deflected by the deflecting unit onto the photoreceiver. The synchronous optical element satisfies a relationship $f_m < f_d$, where f_m is a composite focal length of the scanning optical element in a main scanning direction, and f_d is a composite focal length of the synchronous optical element in the main scanning direction.

FIG.1




FIG.2




FIG.3




FIG. 4




FIG.5




FIG.6




FIG.7




FIG.8


CYLINDRICAL
SURFACE



CYLINDRICAL
SURFACE

FIG.9

CYLINDRICAL
SURFACE



SPHERICAL SURFACE



FIG.10




FIG.11




FIG.12






FIG.15

